

HANSEN

W6000 SERIES

SCREW-TO-CONNECT SELF-SEALING COUPLINGS



- Rugged, one-piece body
- Screw-locking mechanism gives exceptional resistance to severe hydraulic loads
- Automatic shut-off in both halves on disconnection
- Pressure ratings up to 1100 bar (see chart)
- Can be connected against residual pressure*
- Size range 1/4" to 2"
- Available in plated steel and in stainless steel

SOCKETS					
	STEEL	STAINLESS STEEL	o/l	sleeve max o/d	a/f
1/4" BSP	WA0601700	WV06017V0	53	35	19
1/4" NPT	WA0621700	WV06217V0			
3/8" BSP	WA0602700	WV06027V0	65	38	23
3/8" NPT	WA0622700	WV06227V0			
1/2" BSP	WA0603700	WV06037V0	74	45	27
1/2" NPT	WA0623700	WV06237V0			
3/4" BSP	WA0604700	WV06047V0	91	55	35
3/4" NPT	WA0624700	WV06247V0			
1" BSP	WA0605700	WV06057V0	103	69	41
1" NPT	WA0625700	WV06257V0			
1.1/4" BSP	WA0606700	WV06067V0	145	89	55
1.1/4" NPT	WA0626700	WV06267V0			
1.1/2" BSP	WA0607700	WV06077V0	173	100	63
1.1/2" NPT	WA0627700	WV06277V0			
2" BSP	WA0609700	WV06097V0	205	117	71
2" NPT	WA0629700	WV06297V0			

PLUGS				
	STEEL	STAINLESS STEEL	o/l	a/f
1/4" BSP	WA0601400	WV06014V0	35	19
1/4" NPT	WA0621400	WV06214V0		
3/8" BSP	WA0602400	WV06024V0	42	23
3/8" NPT	WA0622400	WV06224V0		
1/2" BSP	WA0603400	WV06034V0	50	27
1/2" NPT	WA0623400	WV06234V0		
3/4" BSP	WA0604400	WV06044V0	63	35
3/4" NPT	WA0624400	WA06244V0		
1" BSP	WA0605400	WV06054V0	71	41
1" NPT	WA0625400	WV06254V0		
1.1/4" BSP	WA0606400	WV06064V0	97	55
1.1/4" NPT	WA0626400	WV06264V0		
1.1/2" BSP	WA0607400	WV06074V0	109	63
1.1/2" NPT	WA0627400	WV06274V0		
2" BSP	WA0609400	WV06094V0	129	71
2" NPT	WA0629400	WV06294V0		



DUST PLUGS AND CAPS		
Size	PLUGS	CAPS
1/4"	WD0611700	WD0611400
3/8"	WD0612700	WD0612400
1/2"	WD0613700	WD0613400
3/4"	WD0614700	WD0614400
1"	WD0615700	WD0615400
1.1/4"	WD0616700	WD0616400
1.1/2"	WD0617700	WD0617400
2"	WD0619700	WD0619400

PRESSURE RATINGS	
Size	Max. w.p.
1/4"	1100 bar
3/8"	750
1/2"	750
3/4"	650
1"	450
1.1/4"	450
1.1/2"	300
2"	300



GUYSON INTERNATIONAL LIMITED
HOSE & COUPLINGS DIVISION

Southview Business Park,
 Guiseley, Leeds LS20 9PR

Tel: 01943 870044 Fax: 01943 870066

Email: leeds@guyson.co.uk Web: www.guyson.co.uk



FS 28046

For pulsating pressures when disconnected apply a multiplier of 0.5
 *max. connecting/disconnecting pressure: 30 bar all sizes