

GENERAL PURPOSE SUCTION AND DELIVERY 10 BAR (150 PSI) - EPDM



4+4 SP
Construction

Tube: Black EPDM

Reinforcement: High tensile textile cords with embedded steel helix wire

Cover: Black EPDM - abrasion and ozone resistant

Use: Mild chemicals and fertilizers suction and delivery in general industrial and agricultural applications

Safety factor: <= 127 mm 3:1 >=152 mm 2,5:1

Temperature: -30 °C +80 °C (-22 °F +176 °F)

mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
19	3/4	29	1,14	10	150	76	3,00	100	0,550	0,370
25	1	35	1,38	10	150	100	4,00	100	0,680	0,460
32	1 1/4	42	1,65	10	150	128	5,00	100	0,810	0,540
38	1 1/2	48	1,89	10	150	152	6,00	100	0,930	0,630
51	2	61	2,40	10	150	204	8,00	100	1,220	0,820
60	2 3/8	72	2,83	10	150	240	9,50	100	1,750	1,180
63	2 1/2	75	2,95	10	150	252	10,00	90	1,760	1,180
76	3	88	3,46	10	150	304	12,00	90	2,100	1,410
90	3 1/2	102	4,02	10	150	360	14,00	90	2,640	1,770
102	4	114	4,49	10	150	408	16,00	90	2,950	1,980
127	5	141	5,55	10	150	635	25,00	80	4,670	3,140
152	6	166	6,54	10	150	760	30,00	80	5,840	3,920
203	8	221	8,70	10	150	1015	40,00	70	9,810	6,590