

SATURATED STEAM 17 BAR (250 PSI)

BS 5342/2A NFT 47263/I3

Tube: Black EPDM

Reinforcement: High tensile steel cords

Cover: Red EPDM - heat, abrasion and ozone resistant - pin pricked

Use: Saturated steam

Safety factor: 10:1

Temperature: -40 °C +210 °C (-40 °F +410 °F)

mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
10	3/8	22	0,87	17	250	100	4,00		0,490	0,330
13	1/2	25	0,98	17	250	130	5,00		0,560	0,380
16	5/8	28	1,10	17	250	160	6,25		0,620	0,420
19	3/4	32	1,26	17	250	190	7,50		0,730	0,490
19	3/4	33	1,30	17	250	190	7,50		0,850	0,570
25	1	38	1,50	17	250	250	10,00		0,900	0,600
25	1	40	1,57	17	250	250	10,00		1,040	0,700
32	1 1/4	46	1,81	17	250	320	12,50		1,320	0,890
32	1 1/4	48	1,89	17	250	320	12,50		1,500	1,010
38	1 1/2	52	2,05	17	250	380	15,00		1,540	1,030
38	1 1/2	54	2,13	17	250	380	15,00		1,740	1,170
51	2	67	2,64	17	250	510	20,00		2,150	1,440
51	2	69	2,72	17	250	510	20,00		2,400	1,610
63	2 1/2	83	3,27	17	250	630	25,00		3,720	2,500
76	3	96	3,78	17	250	760	30,00		4,410	2,960